

THRILL VORTEX F1 PRO LCD

A new dynamical communication that is added to the sanitization, refrigeration and dispersion of odours.



Technical Specifications:


Dimensions	7.87" x 7.87" x 10.12" h (cm 20 x 20 x 25,7 h)
Unit Weight	17.60 lb (8 kg) approx.
Picture and video files format	Pictures: jpg, jpeg, png, bmp Video: mp4, avi, mpg, mpeg
Display	5", 800 x 480 pixels, 108 x 65 mm
File loading	Via USB flash drive (included)
Power Supply	Rechargeable 12V battery - battery life approx. 10 hours
Recharge voltage from mains	100/240 V AC Plug - recharging time approx. 12 hours
Gas Refrigerant	CO ₂ (Food Grade) Carbon Dioxide
Cylinder Type	CO ₂ Cylinder with Siphon tube (not included)
CO₂ Line Standard Length	9.20 feet (mt. 2,80) apporx. (including connection valve)
Frequency	50 – 60 Hz
Max Power Capacity	50 W
Battery Charger	Included

NOTE: To always be associated with the long tube mod. T8 ERT or T12 ERT

All dimensions, specification and characteristics may be subject to change.

CE **MADE IN ITALY** - 100% designed and produced in Italy
Conform to European CE Standards
INTERNATIONAL PCT PATENT

NSF NSF certified product



Designed and Engineered by

THRILL
INTERNATIONAL