



**Self-contained ice maker - Sprayer system**  
**Daily production up to 72 kg**

[illegible]

## ► Features & Plus

- Compact and crystal cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Adjustable Stainless Steel feet
- Removable and cleanable air filter
- Air or water cooling system
- Easy cleanable internal rounded surfaces
- HCFC-Free insulated storage
- RoHS Free
- Disappearing insulated door
- Electromechanical operation
- ON-OFF rocker switch
- Standard and special voltages
- HFC Free
- Automatic Washing system



► Position n°



AISI 304 SS Scotch  
Brite finish



Adjustable Stainless Steel feet




Removable and cleanable air filter



Disappearing insulated door

► Available ice cube size



► Prod. 24h

|                                                                                     |           |       |             |       |    |     |
|-------------------------------------------------------------------------------------|-----------|-------|-------------|-------|----|-----|
|  | Air temp. |       | Water temp. |       | kg | lbs |
|                                                                                     | 10° C     | 50° F | 7° C        | 45° F | 72 | 159 |
|                                                                                     | 21° C     | 70° F | 15° C       | 60° F | 70 | 154 |

**2 Years Warranty**  
subject to limitations

► **Certifications available for this model**






Ice Cube

# CB 674 HC



## Self-contained ice maker - Sprayer system Daily production up to 72 kg



### ► Working conditions

- Location: Indoor

|                      | Min             | Max             |
|----------------------|-----------------|-----------------|
| Ambient temperature  | +10° C / +50° F | +43° C / 110° F |
| Water temperature    | +3° C / +37° F  | +32° C / +90° F |
| Voltage              | -10%            | +10%            |
| Water inlet pressure | 1bar (14 psi)   | 6bar (84 psi)   |

### ► Performances

|                 |       | Water temperature |         |       |         |       |         |
|-----------------|-------|-------------------|---------|-------|---------|-------|---------|
|                 |       | 7° C              | 45° F   | 15° C | 60° F   | 21° C | 70° F   |
|                 |       |                   |         |       |         |       |         |
| Air temperature | 10° C | 72 kg             |         |       |         |       |         |
|                 | 50° F |                   | 159 lbs |       |         |       |         |
|                 | 21° C |                   |         | 70 kg |         |       |         |
|                 | 70° F |                   |         |       | 154 lbs |       |         |
|                 | 32° C |                   |         |       |         | 58 kg |         |
|                 | 90° F |                   |         |       |         |       | 128 lbs |

### ► Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water in.: 116 mm / 4 9/16" - 220 mm / 8 11/16" - 3/4"      ② Water out.: 54 mm / 2 2/16" - 180 mm / 7 1/16" - 24 mm / 15/16"
- ③ Electrical connections: 161 mm / 6 5/16" - 256 mm / 10 1/16"

### ► Technical information

|                           |                            |
|---------------------------|----------------------------|
| Production in 24h         | 70 kg / 154 lbs            |
| Store capacity, up to     | 40 kg / 88 lbs             |
| Cooling system            | A - W                      |
| Kind of cube              | A-18g, C-33g, D-13g, E-42g |
| Refrigerant               | R290                       |
| Standard voltage          | 220-240 V ~ 50 Hz          |
| Average power consumption | 600 W                      |
| Fuse                      | 10 A                       |
| Electrical consumption    | 24 kWh/100kg               |

|                            |                                        |
|----------------------------|----------------------------------------|
| Water consumption          | A: 4 l/kg - 48 gal/100 lbs             |
|                            | W: 15 l/kg - 180 gal/100 lbs           |
| Sizes (L-P-H mm)           | 738 - 600 - 851,5                      |
| (L-P-H in)                 | 29 1/16 - 23 10/16 - 33 8/16           |
| Sizes with pack (L-P-H mm) | 780 - 640 - 1015                       |
| (L-P-H in)                 | 30 11/16 - 25 3/16 - 39 15/16          |
| Net weight                 | 72 kg / 159 lbs                        |
| Gross weight               | 84 kg / 185 lbs                        |
| Finish                     | AISI 304 stainless steel, scotch brite |

All the technical information must be considered at the following conditions:

Sizes without feet  
Standard Cube (18 g)  
Ambient temperature +21° C  
Water temperature +15° C  
Electrical consumption at +32° C (standard voltage)  
Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Rev. 02 - Issued September 2019



[www.bremaice.it](http://www.bremaice.it)  
[info@bremaice.it](mailto:info@bremaice.it)

Bim + Data  
download

